

Distributed by:



[www.Jameco.com](http://www.Jameco.com) ♦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

## 2N3823, 2N3824

Jameco Part Number 38341

## N-Channel Silicon Junction Field-Effect Transistor

- VHF Amplifiers
- Small Signal Amplifiers

Absolute maximum ratings at  $T_A = 25^\circ\text{C}$ 

Reverse Gate Source & Reverse Gate Drain Voltage	- 50 V
Continuous Forward Gate Current	10 mA
Continuous Device Power Dissipation	300 mW
Power Derating	2 mW/ $^\circ\text{C}$

At  $25^\circ\text{C}$  free air temperature:

## Static Electrical Characteristics

		2N3823		2N3824		Process NJ32	
		Min	Max	Min	Max	Unit	Test Conditions
Gate Source Breakdown Voltage	$V_{(BR)GSS}$	- 30		- 50		V	$I_G = - 1 \mu\text{A}, V_{DS} = \emptyset\text{V}$
Gate Reverse Current	$I_{GSS}$		- 0.5		- 0.1	nA	$V_{GS} = - 30\text{V}, V_{DS} = \emptyset\text{V}$
			- 0.5		- 0.1	$\mu\text{A}$	$V_{GS} = - 30\text{V}, V_{DS} = \emptyset\text{V}$ $T_A = 150^\circ\text{C}$
Gate Source Voltage	$V_{GS}$	- 1	- 7.5			V	$V_{DS} = 15\text{V}, I_D = 400 \mu\text{A}$
Gate Source Cutoff Voltage	$V_{GS(OFF)}$		- 8			V	$V_{DS} = 15\text{V}, I_D = 0.5 \text{ nA}$
Drain Saturation Current (Pulsed)	$I_{DSS}$	4	20			mA	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$
Drain Cutoff Current	$I_{D(OFF)}$				0.1	nA	$V_{DS} = 15\text{V}, V_{GS} = - 8\text{V}$
					0.1	$\mu\text{A}$	$V_{DS} = 15\text{V}, V_{GS} = - 8\text{V}$ $T_A = 150^\circ\text{C}$

## Dynamic Electrical Characteristics

Drain Source ON Resistance	$r_{ds(on)}$				250	$\Omega$	$V_{GS} = \emptyset\text{V}, I_D = \emptyset\text{V}$	$f = 1 \text{ kHz}$
Common Source Forward Transconductance	$g_{fs}$	3500	6500			$\mu\text{S}$	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1 \text{ kHz}$
Common Source Forward Transmittance	$ Y_{fs} $	3200				$\mu\text{S}$	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 100 \text{ MHz}$
Common Source Output Conductance	$g_{os}$		35			$\mu\text{S}$	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1 \text{ kHz}$
Common Source Input Capacitance	$C_{iss}$		6		6	pF	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1 \text{ MHz}$
Common Source Reverse Transfer Capacitance	$C_{rss}$		2		3	pF	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1 \text{ MHz}$
Equivalent Short Circuit Input Noise Voltage	$\bar{e}_N$		200			nV/ $\sqrt{\text{Hz}}$	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 10 \text{ Hz}$
Noise Figure	NF		6			dB	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$ $R_G = 1 \text{ M}\Omega$	$f = 10 \text{ Hz}$

## TO-72 Package

Dimensions in Inches (mm)

## Pin Configuration

1 Source, 2 Drain, 3 Gate, 4 Case